

Birch Run Speedway
10945 Dixie Hwy.
Birch Run, Mi. 48415
(989) 624-9778
www.birchrunracing.com



For Tech Questions
call or email Jeff Parsih
at (989)395.0933 or
jeffparish@birchrunracing.com

BIRCH RUN SPEEDWAY 2022 FIGURE 8 RULES

BODIES

Any american made full size 2 wheel drive car or truck chassis is allowed

- A.) Bodies must be as they came from the factory
- B.) Severely rusted panels MUST be replaced.
- C.) Stock panels only, Panels may be replaced with homemade stock-appearing panels from body lines down.
No flat panels.
- D.) No Aluminum Body components.
- E.) All sharp edges must be rolled under.
- F.) No opening up wheel wells beyond stock appearing.
- G.) Hoods may be pinned in front and back. Stock hinges preferred.
- H.) Hoods must open without tools of any kind. Fuel cell area must be accessible without tools.
- I.) All bumpers must be rounded on ends, NO STRAIGHT CUT OR SHARP EDGES.
Stock-type bumpers only. Bumper covers will be allowed. No fabricated bumpers allowed.
- J.) Bumpers must be securely chained to frame, and have a chain loop wrecker hook in center of each bumper.
- K.) All doors must be welded shut.
- L.) All glass except windshield must be removed. Severely cracked windshields MUST BE REPLACED. You may use 1/8 Lexan to replace windshield.
- M.) All trailer hitche inserts and after-market type add-ons must be removed.
- N.) Front fender inner-liners may be removed.
- O.) All interior must be removed, dash covers, seats, headliner, etc.
- P.) No removing of "ANY" sheet metal, frame or frame components (i.e. Floor pans, bumper ear horns).
- Q.) Wings, Spoilers, side boards encouraged. must not effect driver or other drivers vision

ROLLCAGE

- A. A 4-point cage of minimum 1 3/4 OD and .095 wall tubing is required, and MUST remain in interior of the car, and anchored securely to the FRAME.
- B. Full Front and Rear hoops allowed.
- C. Bars may be attached to end of frame rail but may NOT cross (like an X) after the rear axle. Radiator bars are allowed.
- D. A minimum of 3 door bars and a 1/8" steel doorplate must be installed on the driver's side cage. A 1/8" x 18" x 36" steel floor plate is HIGHLY recommended under the driver.

FUEL CELL

- A. Fuel cells are mandatory. TRUCKS may retain factory tank if mounted inside the frame rails
- B. Cell must be located in the trunk secured by 2 straps side-to-side and at least 1 front to rear.
- C. The fuel cell may be no lower than the rear frame rails, 8" ground clearance minimum allowed with safety hoop,
- D. Fuel lines may not pass through driver's compartment

REAR END

- A. Rear ends may be welded or open, Full spool / Mini spools are OK.
- B. No traction control
- C. Stock OEM read

D. Must have a drive shaft loop 1/3 of the way from the front of the drive shaft. (Chain OK).

WHEELS

A. 8" maximum width steel wheels. Any offset is OK. No spacers allowed.

B. 1" lug nuts highly recommended, for safety. At least 1 thread must extend beyond nut