



2023 Figure 8 Rules

Body

Any american made full size 2 wheel drive car or truck chassis is allowed

- A.) Bodies must be as they came from the factory
- B.) Severely rusted panels MUST be replaced.
- C.) Stock panels only, Panels may be replaced with homemade stock-appearing panels from body lines down. No flat panels.
- D.) No Aluminum Body components.
- E.) All sharp edges must be rolled under.
- F.) No opening up wheel wells beyond stock appearing.
- G.) Hoods may be pinned in front and back. Stock hinges preferred.
- H.) Hoods must open without tools of any kind. Fuel cell area must be accessible without tools.
- I.) All bumpers must be rounded on ends, NO STRAIGHT CUT OR SHARP EDGES. Stock-type bumpers only. Bumper covers will be allowed. No fabricated bumpers allowed.
- J.) Bumpers must be securely chained to frame, and have a chain loop wrecker hook in center of each bumper.
- K.) All doors must be welded shut.
- L.) All glass except windshield must be removed. Severely cracked windshields MUST BE REPLACED. You may use 1/8 Lexan to replace windshield.
- M.) All trailer hitche inserts and after-market type add-ons must be removed.
- N.) Front fender inner-liners may be removed.
- O.) All interior must be removed, dash covers, seats, headliner, etc.
- P.) No removing of "ANY" sheet metal, frame or frame components (i.e. Floor pans, bumper ear horns).
- Q.) Wings, Spoilers, side boards encouraged. must not effect driver or other drivers vision

Roll Cage

- A. A 4-point cage of minimum 1 3/4 OD and .095 wall tubing is required, and MUST remain in interior of the car, and anchored securely to the FRAME.
- B. Full Front and Rear hoops allowed.
- C. Bars may be attached to end of frame rail but may NOT cross (like an X) after the rear axle. Radiator bars are allowed.
- D. A minimum of 3 door bars and a 1/8" steel doorplate must be installed on the driver's side cage. A 1/8" x 18" x 36" steel floor plate is HIGHLY recommended under the driver.
- E. Minimum X bar with a top bar on right side door.

Fuel Cell

- A. Fuel cells are mandatory. TRUCKS may retain factory tank if mounted inside the frame rails
- B. Cell must be located in the trunk secured by 2 straps side-to-side and at least 1 front to rear.
- C. The fuel cell may be no lower than the rear frame rails, 8" ground clearance minimum allowed with safety hoop,
- D. Fuel lines may not pass through driver's compartment

Rear End

- A. Rear ends may be welded or open, Full spool / Mini spools are OK.
- B. No traction control
- C. Stock OEM read
- D. Must have a drive shaft loop 1/3 of the way from the front of the drive shaft. (Chain OK)

Wheels

- A. 8" maximum width steel wheels. Any offset is OK. No spacers allowed.
- B. 1" lug nuts highly recommended, for safety. At least 1 thread must extend beyond nut